

ROCK DRILL

Mining Tools / Sinker Drill

ACE RD 330 Wet/Dry Jackleg Drill is water-flushed, pusher leg-mounted rock drill. Rock drills are compatible with a 27 to 41 mm hole diameter range and use a Hex 22 (7/8") rotation shank as a standard. When paired with Ace Pneumatics' tapered button bits, penetration rates can increase by approximately 25-50% compared to traditional integral steels, with a service life that lasts three to five times longer.



TECHNICAL SPECIFICATION:-

Specification	Metric	Imperial
Weight	23 kg	50.7 lb
Length without Leg	609 mm	24"
Impact Rate	2650 BPM	
Piston Stroke	51 mm	2"
Air Pressure	6 Bar	87 PSI
Air Consumption	57 l/s	170 cfm
Air Hose Connection	25 mm	1"
Water Connection	13 mm	1/2"
Hole Size	27-41 mm	1.06" - 1.61"
Shank Size (Hex)	22 X 108 mm	7/8 X 4 ¼"

Note: Dry varient doesn't have water Connection

APPLICATION:-

- BProduction drilling for underground mining and construction
- Tunnel Construction
- Metal Mining Operations



• Note: - All Manufacturer names, part numbers, and descriptions are for reference only; listing does not imply their products. (REV.05 JAN 2025)